

Does Midphase Support CDonts

Cdonts is supported on our Windows hosting plans using classic ASP.

Sending Mail from ASP with CDONTS.NewMail Object

The NewMail object gives you the ability to send a message within an ASP page with only few lines of code. The syntax for sending mail with the NewMail object of CDONTS is as follows:

```
objNewMail.Send( [From] [, To] [, Subject] [, Body] )
```

You can create the instance of NewMail Object with the following code.

```
<%  
Dim objNewMail  
Set objNewMail = Server.CreateObject("CDONTS.NewMail")  
%>
```

Properties of NewMail Object.

From	A string value containing the email address of the sender (for example Me@somewhere.com)
To	A string value containing the email address of the recipient. (for example, someone@somewhere.com) Multiple addresses can be added by separating with ";"
Subject	The subject line for the message.
Body	A string value containing the body text of message.
Cc	A string containing the email addresses of recipients who will receive a copy of current message.
Bcc	A string containing the email addresses of recipients who will receive a blind copy of current message.
Importance	This is an Integer value that represents the priority of message. (for example High, Normal or Low)
BodyFormat	An integer value which sets the text format of NewMail Object. ObjMail.BodyFormat = 0 (HTML format) ObjMail.BodyFormat = 1 (default Plain Text format)
MailFormat	An integer value which sets the encoding of NewMail Object. ObjMail.MailFormat = 0 (Mime format) ObjMail.MailFormat = 1 (default Plain Text format)

Methods of NewMail Object.

AttachFile	This method attaches a file to the current message.
AttachURL	This method attach a file to current message and associate a URL with that attachment.
Send	This method sends the message.

After the send method the NewMail object becomes invalid but stays in the memory.

You should set NewMail Object to nothing and release the memory after the Send method.

After the send method you will have to create a new instance of NewMail Object if you want to send another message.

Let us see how we can use CDONTS.Newmail Object to send mail from an ASP Page.

```

<%
Option Explicit

Dim objNewMail

' First create an instance of NewMail Object
Set objNewMail = Server.CreateObject("CDONTS.NewMail")

' After an instance of NewMail Object has been created.
' If you like you can use this one line of code to send the mail.
objNewMail.Send From, To, Subject, Message
' or you can give every value separate

objNewMail.From = "webmaster@devasp.com"
objNewMail.To = "test@devasp.com"

' Please replace the "From" and "To" email addresses with
your
' own valid email address. I receive too many emails
' from people who test this sample and keep sending
' emails to test@devasp.com, or they keep the "From" property
' as webmaster@devasp.com and I get response of
' undeliverable emails.
' NOTE: If the "To" or "From" properties of CDONTS contain
' invalid email address you will not receive the email.

objNewMail.Subject = "This is a test Mail"
objNewMail.Body = "This is the Body text of this test mail."
objNewMail.Send

' After the Send method, NewMail Object become Invalid
' You should set it to nothing to release the memory

Set objNewMail = Nothing

' If you want to send another mail
' you have to create a new instance of NewMail Object again.

Response.Write "Email has been sent"

%>

```

Related articles

Content by label

There is no content with the specified labels